


2025 MAVERICK R XRS WITH SMART-SHOX




 Carbon Black & Neo Yellow
 Triple Black
 Dusty Navy & Legion Red

ENGINE	999T DCT
Type	240 hp, Rotax® 999T engine, 999 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	Rotax® DCT, 7-speed with high and low range
Drive Train	Lockable front differential with exclusive Smart-Lok* True 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL
Power Steering	Gen 2 Tri-mode DPS™ high torque
SUSPENSIONS	
Front Suspension	Forged-aluminum heavy-duty tall knuckle Double A-arm with sway bar / 25 in. (63.5 cm) suspension travel
Front Shocks	FOX® 2.5 PODIUM® Piggyback with bypass and Smart-Shox** Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound)
Rear Suspension	4-link trailing arm with forged-aluminum heavy-duty tall knuckle / 26 in. (66 cm) suspension travel
Rear Shocks	FOX® 3.0 PODIUM® Piggyback with bypass and Smart-Shox** Technology featuring Live Valve Gen 3 (Dual Valve compression & rebound)
TIRES & WHEELS	
Front / Rear Tires	ITP Tenacity XNR 32 x 10 x 16 in. (NA) XPS Trac Force 32 x 10 x 16 in. (INTL)
Wheels	16 in. aluminum flow-formed beadlock
BRAKES	
Front	32 mm hydraulic triple-piston caliper with a 265 mm disc
Rear	30 mm hydraulic twin-piston caliper with a 255 mm disc

PACKAGE HIGHLIGHTS

- 77 in. 4-link trailing arm with aluminum HD tall knuckle
- Smart-Lok™ front differential
- FOX® 3.0 PODIUM® Piggyback with bypass and Smart-Shox** Technology featuring Live Valve Gen 3 (dual-valve compression and rebound)
- 10.25 in. touchscreen display
- 32 in. ITP Tenacity XNR tires
- 16 in. flow-formed beadlock wheels
- Front and rear camera
- Telescopic steering wheel with infotainment controls
- Full hard roof
- Full plastic skid plates
- 4-point harness with shoulder pads
- Premium high-performance LED headlights
- Can-Am LED signature
- Center dashboard storage with cell phone holder
- X package graphics / seats
- 1,700 W magneto

DIMENSIONS & CAPACITIES

Estimated Dry Weight	2,250 lb (1,020 kg)
Chassis / Cage	High-strength (dual-phase) steel tubing and stampings
L x W x H	140 x 78.1 x 71.5 in. (355.6 x 198.5 x 181.5 cm)
Wheelbase	108 in. (274.3 cm)
Ground Clearance	17 in. (43.2 cm)
Rack Capacity	200 lb (90 kg)
Storage Capacity	Total: 2.1 gal (8.1 L)
Fuel Capacity	13.2 gal (50 L)

FEATURES

Gauge	4.5 in. wide digital display with keypad and 10.25 in. touchscreen display
Instrumentation	USB A (2 charging port & 1 communication port) DC outlet (10-A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	Premium high-performance LED headlights Can-Am LED signature
Winch	Winch-ready bumper (4,500 lb / 2,041 kg winch not installed)
Magneto	1,700 W
Protection	Full hard roof Premium half doors Front lower deflector Front / rear anchor Full plastic skid plate

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months

can-am®

© 2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. †Visco-Lok is a trademark of GKN Viscodrives GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SxS) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly. *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry. **Smart-Shox was developed in conjunction with FOX and Tractive Industries, a market leader in the suspension industry.

